

Kune - Enhancement #296

Websocket configurable in a different port and/or subdomain

06/14/2012 09:59 PM - Vicente J. Ruiz Jurado

Status:	Closed	Start date:	
Priority:	Normal	Due date:	
Assignee:		% Done:	100%
Category:	WIAB Server	Estimated time:	0.00 hour
Target version:	0.2.0	Tags:	
Resolution:			
Description			
<p>The idea is that the client uses two configurable listening addresses:</p> <ul style="list-style-type: none">• one for the normal traffic (all the common server petitions), the current http_frontend_public_address• and a new one for the websocket traffic (that can be configured to a different subdomain or port if it's necessary). <p>That is, we would be able to split these two different traffics. This would allow the use of proxies, caches or CDNs for the "normal traffic".</p> <p>https://issues.apache.org/jira/browse/WAVE-357</p>			

History

#1 - 06/14/2012 09:59 PM - Vicente J. Ruiz Jurado

- Status changed from New to Resolved
- % Done changed from 0 to 80

#2 - 06/15/2012 03:59 AM - Stanislav German-Evtushenko

Fixed in commit:9da117c8

#3 - 08/19/2012 09:57 PM - Vicente J. Ruiz Jurado

- Status changed from Resolved to Closed
- % Done changed from 80 to 100